

Hazard Register



Type	RIDE ON ELECTRIC PALLET MOVER	Location	Grays Online
Make	-	Sale Number	5051359
Model	-	Lot Number	22
Serial Number			

ID	Hazard Type	Hazard Description
134445.1	Work Method	HANDBRAKE MUST BE APPLIED, MOTOR KEY SWITCHOFF AND REMOVED WHEN THE PLANT IS LEFT UNATTENDED.
134445.3	Plant Operation	CONDUCT AND DOCUMENT REGULAR ON-SITE INSPECTIONS OF THE PLANT CONDITION i.e LIGHTS, HAZARD WARNING DEVICES, TYNES, TYRES, BRAKES. TYRES ARE BALD AND SHOULD BE REPLACED.
134445.4	Plant Operation	PLANT SHOULD BE USED AND ACCESSED BY COMPETENT/SKILLED (FORKLIFT OPERATOR) PERSONNEL ONLY.
134445.5	Signage	SAFE WORKING LOAD LABEL SHOULD ALWAYS BE ATTACHED TO FRONT OF FORKLIFT.
134445.6	Plant Operation	ALWAYS TEST REVERSING LIGHTS AND ALARMS ON A SCHEDULED BASIS. DOCUMENT REGULAR ON-SITE TESTING OF ALL HAZARD WARNING DEVICES.
134445.7	Plant Operation	NO MAINTENANCE OR SERVICE RECORDS AVAILABLE
134445.9	Signage	ATTACH CLEAR & VISIBLE 'NO SMOKING ' SIGN TO PLANT.
134445.10	Visibility	FORKLIFT SHOULD HAVE A REVERSING MIRROR FITTED TO PLANT IN SUITABLE POSITION TO OPERATOR.
134445.11	Ergonomics	A DRIVERS SEAT BELT SHOULD ALWAYS BE FITTED AND WORN BY ALL OPERATORS.
134445.12	Noise	SOUND PRESSURE LEVELS (SPL) NEED TESTING AT OPERATOR STATION. IF SPL GREATER THAN 85 dB(A), CLEAR & VISIBLE WARNINGS MUST BE ATTACHED re USE OF HEARING PROTECTION.
134445.13	Plant Operation	ATTACH SAFE OPERATING INSTRUCTIONS IN A CLEAR AND VISIBLE POSITION TO OPERATOR, INCLUDING BATTERY CHARGING INSTRUCTIONS.
134445.14	Plant Operation	PLANT TO BE OPERATED IN DESIGNATED AREAS ONLY (I.E. FIRM/STABLE/LEVEL GROUND).
134445.15	Work Method	A MOBILE PLANT TRAFFIC MANAGEMENT PLAN MUST BE PREPARED TO ENSURE THE SAFETY OF PEDESTRIAN, VISITORS, OTHER VEHICLE MOVEMENTS AND PROPERTY ETC, BEFORE THE PLANT IS USED IN THE WORKPLACE.
134445.16	Plant Operation	ROLLOVER PROTECTION IS FITTED. ENSURE THIS IS CERTIFIED TO AS1636 TO ENSURE THE SAFETY OF OPERATORS FROM FALLING OBJECTS OR ROLLOVER.
134445.17	Plant Operation	PROVIDE COMPETENCY BASED TRAINING AND FORMALISED ASSESSMENT AS REQUIRED BY WORKCOVER. DOCUMENT RESULTS OF TRAINING. PLANT TO BE USED BY COMPETENT AND LICENSED PERSONNEL ONLY.
134445.18	Guarding	ASSESS PLANT FOR ENTANGLEMENT AND ENTRAPMENT HAZARDS WITHIN THE WORKPLACE. rISK ASSESS HAZARDS AS PER AS4360:2004 RISK MANAGEMNET AND IMPLEMENT APPROPRIATE CONTROLS.
134445.19	Manual Handling	ENSURE ALL MANUAL HANDLING TASKS ASSOCIATED WITH MACHINE OPERATION AND MAINTENANCE ARE IDENTIFIED AND ASSESSED AND SUITABLE CONTROLS AS REQUIRED IN AS4360:2004 RISK MANAGEMENT ARE IMPLEMENTED.

Health and Safety Plant Safety Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

Likelihood	Consequences
<ul style="list-style-type: none">• Frequency and duration of exposure• Probability of occurrence of hazard or event (including part history of incidents)• Possibility to avoid / minimize or limit the damage, impact or harm• Reliability and effectiveness of existing / established systems of control	<ul style="list-style-type: none">• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area• Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.