

Hazard Register



| | | | |
|----------------------|----------|--------------------|---------|
| Type | MORTICER | Location | |
| Make | - | Sale Number | 5057761 |
| Model | - | Lot Number | 20 |
| Serial Number | | | |

| ID | Hazard Type | Hazard Description |
|-----------|-----------------|--|
| 142563.1 | Electrical | PLANT TO BE USED WITH AN ELECTRICAL CIRCUIT BREAKER (SAFETY SWITCH) AND OVERLOAD PROTECTION. |
| 142563.2 | Guarding | MOVING PARTS OF THE PLANT MAY ENTRAP OR CUT BODY PARTS. ALL FIXED AND OPERABLE GUARDS MUST BE REPLACED AFTER MAINTENANCE/CLEANING ACTIVITIES. ENSURE ANY IN PLACE INTERLOCKING SWITCHES ARE ROUTINELY CHECKED/SERVICED GUARDING SHOULD BE IN ACCORDANCE WITH AS4024.1: SAFEGUARDING OF MACHINERY. |
| 142563.3 | Manual Handling | HANDLING OF WORKPIECES ON/OFF THE PLANT. CONDUCT MANUAL HANDLING RISK ASSESSMENT FOR TASK(S) ASSOCIATED WITH THE OPERATION OF THE PLANT. |
| 142563.4 | Plant Structure | PLANT TO BE MOUNTED/FIXED INTO POSITION AS PER MANUFACTURER'S INSTRUCTIONS |
| 142563.5 | SLIP TRIP FALL | ENSURE WORKSPACE AROUND PLANT IS KEPT CLEAR OF OBSTACLES AND MAINTAINED IN A NEAT AND TIDY CONDITION. |
| 142563.6 | Electrical | PLANT NEEDS TO BE REGULARLY INSPECTED AND MAINTAINED AS PER AS/NZS3760: IN-SERVICE SAFETY INSPECTION AND TESTING OF ELECTRICAL EQUIPMENT AND AS/NZS3000: WIRING RULES AND/OR AS1543: ELECTRICAL EQUIPMENT OF INDUSTRIAL MACHINES. |
| 142563.7 | Thermal | FRICITION / ABRASION / DISINTEGRATION / COMING INTO CONTACT WITH BELT DURING OPERATION. ENSURE SIGNAGE IS ATTACHED ADJACENT TO PLANT INSTRUCTING OPERATOR TO "KEEP BODY PARTS (HANDS ECT) CLEAR DURING PLANT OPERATION. |
| 142563.8 | Training | PROVIDE ANY MANUFACTURER'S MANUALS/INSTRUCTIONS FOR THE PLANT |
| 142563.9 | Entanglement | ENTANGLEMENT/RUN-DOWN - DO NOT PLACE HANDS OR OTHER PARTS OF THE BODY NEAR ROTATING PARTS OF THE PLANT WHEN SETTING UP AND/OR FEEDING MATERIAL FOR THE PLANT. DO NOT USE WHEN WEARING LOOSE CLOTHING. |
| 142563.10 | Air Quality | AIRBORNE DUST PARTICLES ASSOCIATED WITH PLANT AND/OR PROCESS. DUST EXTRACTION SYSTEM TO BE FITTED AND PROVIDE EYE AND BREATHING PPE AS APPROPRIATE. |
| 142563.11 | PPE | PERSONAL PROTECTIVE EQUIPMENT (PPE) - IDENTIFY TYPE AND PROVIDE INSTRUCTION/INFORMATION RE: USE, STORAGE, CARE AND MAINTENANCE OF PPE (E.G. EYE & HEAR PROTECTION, DUST MASK ETC.) |
| 142563.12 | Instructions | ATTACH OPERATING INSTRUCTIONS IN A CLEAR AND VISIBLE POSITION TO OPERATOR. |
| 142563.13 | Skills | PLANT TO BE USED AND ACCESSED BY COMPETENT/TRAINED/SKILLED PERSONNEL ONLY. |
| 142563.14 | Signage | OPERATOR INJURY MAY RESULT FROM ILLEGIBLE OR MISSING WARNING LABELS/SIGNAGE (NOISE, PPE, OPERATING INSTRUCTIONS, HOT SURFACES, EXITS, ROTATING FANS, NIP POINTS ECT). REGULAR INSPECTION & REPLACEMENT OF WARNING LABELS (SAFETY DECALS) IS REQUIRED. * NOTE: NEEDS MORE SAFETY SIGNAGE DISPLAYED ON AND AROUND MACHINE. |

Hazard Register



| | | |
|-----------|-------------------|--|
| 142563.15 | Plant Operation | ENERGY SOURCES ASSOCIATED WITH THE PLANT (ELECTRICAL) TO BE ISOLATED WHEN THE PLANT IS BEING CLEANED/MAINTAINED. |
| 142563.16 | Noise | SOUND PRESSURE LEVELS NEED TESTING AT OPERATOR STATION. IF SPL GREATER THAN 85 dB(A), CLEAR & VISIBLE WARNINGS MUST BE ATTACHED RE: USE OF HEARING PROTECTION. |
| 142563.17 | Plant Maintenance | CONDUCT REGULAR DOCUMENTED SERVICE/INSPECTION OF THE PLANT. MAINTAIN RECORDS OF CHANGES/MODIFICATIONS MADE TO THE PLANT. |

Health and Safety Plant Safety Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

| Likelihood | Consequences |
|--|---|
| <ul style="list-style-type: none">• Frequency and duration of exposure• Probability of occurrence of hazard or event (including part history of incidents)• Possibility to avoid / minimize or limit the damage, impact or harm• Reliability and effectiveness of existing / established systems of control | <ul style="list-style-type: none">• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area• Are temperatures of plant, or chemicals, likely to further injure entrapped person |

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.