

Hazard Register



Type	FUEL POWERED VIBRATORY TOOL	Location	
Make	GENERIC	Sale Number	1967
Model	Generic	Lot Number	
Serial Number			

ID	Hazard Type	Hazard Description
107560.1	Vibration	VIBRATION - RISK ASSESS THE VIBRATION FOR THIS PLANT AND OR JOB. ENSURE PLANT IS REGULARLY MAINTAINED. ROTATE OPERATORS FREQUENTLY. APPROPRIATE PPE IS TO BE OBTAINED AND WORN E.G. VIBRATION GLOVES.
107560.2	PPE	PERSONAL PROTECTIVE EQUIPMENT (PPE) - IDENTIFY TYPE AND PROVIDE INSTRUCTION/INFORMATION RE: USE, STORAGE, CARE AND MAINTENANCE.
107560.3	Plant Operation	ALL ENERGY SOURCES ASSOCIATED WITH THE PLANT TO BE ISOLATED WHEN PLANT IS CLEANED/MAINTAINED. ALL (INCL. OPENABLE) GUARDS TO BE REPLACED/FITTED BEFORE THE PLANT IS PUT BACK INTO SERVICE.
107560.4	Air Quality	DUST PARTICLES AND OTHER CHEMICALS ASSOCIATED WITH THE PLANT. DOCUMENT RISK ASSESSMENT, REFER TO MSDS. CONSIDER WETTING OF SURFACES TO MINIMISE GENERATION OF DUST.
107560.5	Signage	ALL OPERATOR CONTROLS AND LEVERS TO BE CLEARLY IDENTIFIED AND LABELLED.
107560.6	Work Space	DRILLING AREA - DEBRIS, SLIPPERY SURFACES, ISOLATE WORK AREA WITH BARRICADES AND SIGNS AND CLEAN UP FREQUENTLY
107560.7	Plant Operation	NO SERVICE OR MAINTENANCE RECORDS AVAILABLE. PROVIDE/REFER TO ANY MANUFACTURER'S MAINTENENCE, OPERATIONAL AND/OR INSTRUCTION MANUAL.
107560.8	Plant Operation	ATTACH OPERATING INSTRUCTIONS IN A CLEAR AND VISIBLE POSITION TO OPERATOR.
107560.9	Plant Structure	STABILITY OF THE APPLIANCE AND OR ATTACHMENTS TO THE PLANT/APPLIANCE, ENSURE THE PLANT IS PROPERLY RESTRAINED/SUPPORTED.
107560.10	Signage	ATTACH CLEAR AND VISIBLE HAZARD WARNINGS re HOT SURFACES, SHARP EDGES AND USE OF EYE, FACE PROTECTION.
107560.11	Plant Structure	PLANT INCL. TOOLS TO BE REGULARLY CHECKED AND CONDITION DOCUMENTED. MAINTAIN RECORDS OF ANY MODIFICATION/CHANGES MADE TO THE PLANT.
107560.12	Skills	PLANT TO BE USED AND ACCESSED BY COMPETENT/SKILLED PERSONEEL ONLY.
107560.13	Noise	SOUND PRESSURE LEVELS NEED TESTING AT OPERATOR STATION. IF SPL GREATER THAN 85 dB(A), CLEAR & VISIBLE WARNINGS MUST BE ATTACHED re USE OF HEARING PROTECTION.
107560.14	Signage	CONSIDER THE NEED TO ATTACH HAZARD WARNING SIGN RE: HOT SURFACES (DRILL AFTER EXTENDED USE, BITS/TOOLS AND WORKPIECE).
107560.15	FLAMMABLE SUBSTANCES.	FIRE. ENSURE THAT THE CORRECT FUEL TYPE IS USED IN THIS PLANT. ENSURE THE MATERIAL SAFETY DATA SHEET IS OBTAINED FOR SAFETY INSTRUCTIONS BEFORE USING FALMMABLE LIQUIDS IN THIS PLANT. USE OF AN ENCLOSED SPOUT DISPENSER IS RECOMMENDED. ENSURE FUEL CAP IS SECURED PRIOR TO STARTING THE PLANT.

Health and Safety Plant Safety Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

Likelihood	Consequences
<ul style="list-style-type: none">• Frequency and duration of exposure• Probability of occurrence of hazard or event (including part history of incidents)• Possibility to avoid / minimize or limit the damage, impact or harm• Reliability and effectiveness of existing / established systems of control	<ul style="list-style-type: none">• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area• Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.