

Hazard Register



Type	MULCHER ATTACHMENT	Location	
Make	-	Sale Number	1967
Model	-	Lot Number	-
Serial Number		Vendor	---

ID	Hazard Type	Hazard Description
143233.2	Work Method	ENSURE OPERATORS OBSERVE THE FOLLOWING SAFETY PROCEDURES. 1) ALWAYS SHUT DOWN EQUIPMENT BEFORE MAKING REPAIRS OR ADJUSTMENTS. 2) REGULARLY CHECK THE CONDITION OF THE APPLIANCE GUARDING COMPONENTS 3) WEAR CLOSE FITTING CLOTHES AND TIE UP LONG HAIR WHEN WORKING WITH EQUIPMENT 4) ALWAYS WALK AROUND AND NOT OVER OPERATING EQUIPMENT.
143233.3	Floor Condition	SLIP/TRIP/FALL DUE TO CLIMATE CONDITIONS AND OR GROUND CONDITIONS IN THE VICINITY OF THE PLANT. ENSURE OPERATOR WEARS PROTECTIVE FOOTWEAR.
143233.4	Mechanical	ENTANGLEMENT IN ROTATING BLADES. NEVER ATTEMPT TO REPAIR ADJUST, OR UNPLUG EQUIPMENT WITH THE HYDRAULIC LINES ENGAGED.
143233.5	Guarding	CUTS ENTANGLEMENT AND AMPUTATION INJURIES FROM BLADES AND SHARP EDGES OF ATTACHMENTS. . ENSURE THAT POWERED ATTACHMENTS ARE ADEQUATELY GUARDED TO PREVENT CONTACT WITH CUTTING, RIPPING, SLASHING MECHANISMS. ENSURE CHAIN CURTAINS IN PLACE ON FRONT AND BACK OF THIS PLANT.
143233.7	Clothing	ENTANGLEMENT WITH ROTATING PARTS ALWAYS RESULTS IN SERIOUS INJURY AND/OR DEATH. ENSURE OPERATORS WEAR CLOSE FITTING CLOTHING, BOOTS WITHOUT LACES AND SECURE LONG HAIR TO PREVENT ENTANGLEMENT.
143233.8	Mechanical	UNINTENDED MOVEMENT OF THE PLANT AND OR MACHINERY. ALWAYS DISENGAGE THE HYDRAULICS, SHUT OFF THE SKID STEER ENGINE AND REMOVE THE KEYS PRIOR TO LEAVING THE PLANT'S SEAT.
143233.9	Plant Operation	PRIOR TO STARTING UP EQUIPMENT AND WITH THE HYDRAULICS DISENGAGED CHECK THE CONDITION OF HYDRAULICS GUARDING. IDENTIFY NICKS, DENTS, BENT COMPONENTS. TEST FOR FREE MOVEMENT OF THE TUBULAR GUARD ON ITS BEARINGS. REPLACE ANY DAMAGED OR DEFECTIVE GUARDING.
143233.10	Controls	ENSURE DOCUMENTED INSTRUCTIONS ARE PROVIDED FOR THE PLANT .
143233.13	Signage	ENSURE SAFETY LABELS PRESENT E.G HAND HAZARD, FLYING DEBRIS, PTO ENTANGLEMENT HAZARD. RISK ASSESS PLANT AND IMPLEMENT APPROPRIATE LABELS AND ENSURE THAT ALL SAFETY LABELS ARE EASILY READ.
143233.14	Crushing	ENSURE THAT THERE ARE NO PERSONS IN CLOSE VICINITY TO THE ATTACHMENT WHEN LOWERING. LOWER ATTACHED IMPLEMENT PRIOR TO LEAVING THE CAB OF THE PLANT.
143233.15	HIGH PRESSURE	EYE DAMAGE, SKIN INJECTION. ENSURE THAT THE HYDRAULIC PRESSURE IS RELEASED PRIOR TO CONDUCTING MAINTENANCE. INSPECTIONS ON HOSES, LINES AND FITTINGS ARE TO BE CONDUCTED REGULARLY.
143233.16	Striking	ENSURE THAT ARM IS LOWERED TO GROUND PRIOR TO INSPECTION OR MAINTENANCE. ENSURE THAT THE OPERATORS PROVIDE AN EXCLUSION ZONE AROUND THE OPERATION ARM. NO PERSONS IS TO BE BELOW THE HYDRAULIC ARM AT ANY TIME.

Health and Safety Plant Safety Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

Likelihood	Consequences
<ul style="list-style-type: none">• Frequency and duration of exposure• Probability of occurrence of hazard or event (including part history of incidents)• Possibility to avoid / minimize or limit the damage, impact or harm• Reliability and effectiveness of existing / established systems of control	<ul style="list-style-type: none">• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area• Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.