

**Sale 5008321 - Preliminary Catalogue - Items May Be Subject to Change**

Lot No.	Units	Description
9	1	Brake Press, Gasparini, PSG200 4000, Synchro, DOM: 1997, S/No. 05973430, 200 tonne, 4100mm bending length 18.5kW, foot pedal control adjustable stroke 250mm fitted with Delem DA24E graphical control panel and lasersafe optical guarding, overhead fluorescent lighting, complete with assorted tooling, overall weight approx 20 tonne, 415 volt hardwired. (1-24). Located inside first roller door. Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
10	1	Brake Press, Amada Promecam, Model ITP5100.30 P81120, 100 tonne, DOM: 1988, 3000mm bending length, 11kW, 400mm throat, adjustable back stop approx 620mm, foot pedal control, fitted with Promecam CNC EMA control panel and lasersafe optical guarding, overhead fluorescent lighting, complete with assorted tooling, overall weight approx 6.6 tonne, 415 volt hardwired. (1-23). Located inside first roller door. Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
11	1	Brake Press, Muratec Toyo, 56 tonne, AOB5620W, approx 2000mm wide bending length, adjustable back step, stoke length 100mm, foot pedal control with Toyo TNC-ACII control panel and Sick 14-FGS optical machine guarding and associated gates, 4 guards. Note: Not operational, computer problems. (1-4). Located opposite rest rooms Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
12	1	Laser Cutter, Cincinnati, Model CL-7075X10, S/No. 49628, DOM: 1996, table approx 3000mm x 1500mm with twin exchange beds 1/2" cutting capacity, 96" X axis travel, 49" Y axis travel, Rofin Sinar 2000 SMX Laser power source, S/No. 302000, DOM: 1996, Cincinnati computer control panels, 415 volt hard wired, overall size approx 11.5 mtrs x 3 mtrs and fitted with pressure sensitive machine lockout mats and a Koolant Kooler Circulating System HCV 12,000-2PR-NF-2FILT, S/No. 10270. Note: This item is hard wired – purchaser will be required to provide a licensed electrician to disconnect and make safe. Copies / evidence of insurances and licenses will be required prior to any work being undertaken.
13	1	Laser Cutter Cincinnati, Model CL-7074X8, S/No. 50248, DOM: 1997, table approx 1200mm x 2400mm, with twin exchange beds, 1/2" cutting capacity, 96" X axis travel, 49" Y axis travel Rofin Sinar 2000 SMX laser power source, S/No. 521000, DOM: 1997, Cincinnati computer control panel, 415 volt hard wired, overall size approx 10 mtrs x 2.5 mtrs and fitted with pressure sensitive machine lockout mats, and a Koolant Kooler Cooling System, HCV 12000-2PR-NF-2 FILT, S/No. 11417, Val No. (1-20) Note: This item is hard wired – purchaser will be required to provide a licensed electrician to disconnect and make safe. Copies / evidence of insurances and licenses will be required prior to any work being undertaken.
14	1	Roots Blower, Leybold (suits Cincinnati SM2000 Laser Cutters) RUVAC, Type WSLF 1001 N: 11794 HTCL 2100, S/No. 3000053U475 Flow rate 1000 m3/h, max diff pressure 80m bar. Note: Refurbished unit (Germany)
16	1	Deburrer, Fladder Auto, Model AUT-1000 VAC, DOM: 2004, S/No. 1198 variable speed, 6 x head, 1000mm infeed belt width, 415 volt hard wired, approx overall size 1800mm x 1800mm x 2200mm(H), approx 1500kg with 6 x abrasive wheels, 350mm, connected to TORT dust extraction unit, cartridge type and ducting, approx size 1270mm x 780mm x 2040mm(H). (1-83), Located under Mezzanine Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
17		CNC Stud Welder, Soyer, Model KTS-1550CNC, S/No. 422-015/04, X -1100MM, Y - 1500mm, Z - 150mm, with 2 x Soyer SK-SAP welding heads, fed by 2 x Soyer BMS-10P modules and 1 x Soyer BMK 161 module with 2 x Soyer UVR-300 parts feeders, work bed size approx 2100mm x 1300mm, controlled by remote digital truck button panel, 415 volt. (1-58). Note: Located on Mezzanine Floor
18	1	Water Purifier, Leyco HLA 2800 EW, Wassertechnik GmbH with approx 54 kgs of one way gel

**Sale 5008321 - Preliminary Catalogue - Items May Be Subject to Change**

Lot No.	Units	Description
19	1	Water Purifier, Leyco HLA 2800 EW, Wassertechnik GmbH with approx 45kg of one way gel
20	1	Brake Press, Muratec Toyo Model APB-284, 400mm(w) press surface, foot pedal control powered by Okuma-BL, 6kW motor, with a Toyer TNC-AC1 digital control panel, overhead fluorescent work light, 415 volt hard wired, top lifting holes. (1-50) Note: Non operational - Located on Mezzanine Floor. Note: This item is hard wired – purchaser will be required to provide a licensed electrician to disconnect and make safe. Copies / evidence of insurances and licenses will be required prior to any work being undertaken.
21	1	Brake Press Muratec Toyo Model AP13-286, 600mm(w) press surface, foot pedal control, powered by Okuma-BL 6kW motor with a Toyo TNC-AC1 digital control panel, SICK 14-FGS optical safety system and mesh guarding, overhead fluorescent work light, 415 volt hard wired, top lifting holes. (1-51). Note: Located on Mezzanine Floor. Note: This item is hard wired – purchaser will be required to provide a licensed electrician to disconnect and make safe. Copies / evidence of insurances and licenses will be required prior to any work being undertaken.
22	1	Brake Press Muratec Toyo Model AP13-286, 600mm(w) press surface, foot pedal control, powered by Okuma-BL, 6kW motor with a Toyo TNC-AC1 digital control panel, SICK 14-FGS optical safety system and mesh guarding, overhead fluorescent work light, 415 volt hard wired, top lifting holes. (1-51). Note: Located on Mezzanine Floor. Note: This item is hard wired – purchaser will be required to provide a licensed electrician to disconnect and make safe. Copies / evidence of insurances and licenses will be required prior to any work being undertaken.
23	1	Brake Press Muratec Toyo Model AP13-286, 600mm(w) press surface, foot pedal control, powered by Okuma-BL, 6kW motor with a Toyo TNC-AC1 digital control panel, SICK 14-FGS optical safety system and mesh guarding, overhead fluorescent work light, 415 volt hard wired, top lifting holes. (1-51). Note: Located on Mezzanine Floor. Note: This item is hard wired – purchaser will be required to provide a licensed electrician to disconnect and make safe. Copies / evidence of insurances and licenses will be required prior to any work being undertaken.
24	1	Brake Press Muratec Toyo Model AP13-286, 600mm(w) press surface, foot pedal control, powered by Okuma-BL, 6kW motor with a Toyo TNC-AC1 digital control panel, SICK 14-FGS optical safety system and mesh guarding, overhead fluorescent work light, 415 volt hard wired, top lifting holes. (1-51). Note: Located on Mezzanine Floor. Note: This item is hard wired – purchaser will be required to provide a licensed electrician to disconnect and make safe. Copies / evidence of insurances and licenses will be required prior to any work being undertaken.
25	1	Brake Press, Muratec Toyo Model APB-284, 400mm(w) press surface, foot pedal control powered by Okuma-BL, 6kW motor, with a Toyer TNC-AC1 digital control panel, overhead fluorescent work light, 415 volt hard wired, top lifting holes. Protected by Toyo SW electronic safety system. (1-50) Note: Non operational - Located on Mezzanine Floor. Note: This item is hard wired – purchaser will be required to provide a licensed electrician to disconnect and make safe. Copies / evidence of insurances and licenses will be required prior to any work being undertaken.
26	1	Laser Engraver, Epilog Model 6000/30 laser engraver, DOM: 2000, S/No. 6050-00010332, 240 volts with computer and software, YUMA pump, Dell 13" monitor, overall size 1070 x 850 x 90mm(H)
30	1	Insertor Press, Haeger Model One Touch 824-OT-2H, DOM: 2003, S/N 80T20506, 8 tonne capacity, foot pedal operation, fitted with Haeger Insertion Logic digital control panel and 2 x Haeger twin module auto feed system MAS-D-2, 415 volt plugged, top lifting lug. (1-54). Note: Located on Mezzanine Floor
31	1	Insertor Press, Haeger (model and serial number not visible) fitted with Haeger tool protection system, foot pedal operation, analogue counters with Haeger module auto feed system, top lift lugs, 415 volt plugged. (1-55) Note: Located on Mezzanine Floor
32	1	Insertor Press, Haeger Model HP6-CE, S/No. 2200, 6 tonne capacity, foot pedal operation, analogue counter. (1-56). Note: Located on Mezzanine Floor

**Sale 5008321 - Preliminary Catalogue - Items May Be Subject to Change**

Lot No.	Units	Description
33	1	Insertor Press, Haeger 618 Model 618-1H, DOM: 1997, S/No. 06H00503, 6 tonne capacity fitted with Haeger tool protection system, foot pedal operation, analogue counters, with Hager module auto feed system MAS-2, top lift lugs, 415 volt plug in. (1-53). Note: Located on Mezzanine Floor
34	1	Insertor Press, Haeger 618 Model 618-1H, DOM: 1998 S/No. 06H00555, 6 tonne capacity fitted with Haeger tool protection system foot pedal operation, analogue counters with Haeger module auto feed system, MAS- 2 RF, work light, top lift lug, 415 volt plug in. (1-53). Note: Located on Mezzanine Floor.
35	1	Tool Grinder, G&N Mate Stemtechnik VTG-II, S/No. 516545, DOM: 2005, 415 volt hard wired touch pad, digital display control box, mounted on metal 6 x drawer storage unit, overall size approx 760mm x 650mm x 1860mm(H), 300kg weight. Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
36	1	Press Brake, Muratec Toyo APB 3613W, 1300mm bend surface, touch button, digital control panel, Toyokoki, fitted with Toyo optical guarding, 415 volt hardwired, (1-41). Note: Not operational, suit parts only. Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
37	1	Rotating Production Table, Kuhlmeier Type WP, mobile, 415 volt plug in with suction rotating jig, 440mm x 550mm, approx weight 600kg fitted with top lifting lug.
38	1	Granite Surface Table, WBJ, 1010mm x 1010mm x 155mm(D) on fabricated angle steel table. (1-86)
39	1	Inspection Unit, Fabrivation, 4600 metal soft, S/No. 96D, table size 4' x 6' with 8 x cameras, DOM: 1995, PC operated, approx overall dimensions 1500mm x 2640mm x 1700mm(H) with 2 x twin manual suction lifters, fork tyne slots. Note: Not operational, believed to have computer problems. (1-85)
40	1	Dust Extraction System, Eurofilter, Asia Pacific Model EFC36, DOM: 2006 powered by 11kW fan motor, 6 x cartridge filters, features Badger fire suppression unit, digital control panel. Includes duct work to linishing area below, 415 volts. Overall size - Unit 1 - 1800mm x 1000mm x 2300mm(H) and Unit 2 - 1650 x 600 x 1350mm(H) fitted with top lifting lugs. (1-57) Note: Located on Mezzanine Floor. Important Notes: 1) Extraction / removal of plant from this site must be undertaken in a manner compliant with all relevant NSW OH and S legislation / regulations and codes of practice. A satisfactory "Safe Work Method Statement" (SWMS example available in the OH and S section of the sale overview) and copies / evidence of insurances and licenses will be required prior to any work being undertaken. Pre approved contractors details are available on the overview. 2) This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
41	1	Dust Extraction Unit, Donaldson Torit Downflo Model DFT4-16, S/No. TG465044-011, contains 8 x cartridge filters, bottom discard, Torit Checker Board, wall mounted control panel, 415 volts, with approx 25 mtrs of ceiling suspended ducting to Cincinnati laser cutter. Located on factory floor. Overall size of unit approx 1000mm x 2000mm x 3800mm(H). (1-52). Note: Located on Mezzanine Floor. Important Notes: 1) The exhaust on this item will be disconnected from the roof and the roof repaired by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to collection that these works have been completed. 2) This unit requires you to work above 2 metres. Therefore you will need to comply with all Work at Heights Regulations. A Safe Work Method Statement (SWMS) may also be required. All requirements for Safe Work at Heights are to be met as per NSW OHS Act and Regulations. 3) This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.

**Sale 5008321 - Preliminary Catalogue - Items May Be Subject to Change**

Lot No.	Units	Description
42	1	Dust Extraction Unit, Donaldson Torit Downflo, Model DFT2-16, S/No. IG373194-0022, contains 8 x cartridge filters, bottom discard, Torit Checker Board, wall mounted control panel, 415 volts with approx 20 mtrs of ceiling suspended ducting, to Cincinnati laser cutter, located on factory floor. Overall dimensions of unit approx 100mm x 2000mm x 3800mm(H). (1-52). Note: Located on Mezzanine Floor. Important Notes: 1) The exhaust on this item will be disconnected from the roof and the roof repaired by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to collection that these works have been completed. 2) This unit requires you to work above 2 metres. Therefore you will need to comply with all Work at Heights Regulations. A Safe Work Method Statement (SWMS) may also be required. All requirements for Safe Work at Heights are to be met as per NSW OHS Act and Regulations. 3) This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
43	1	Dust Extractor, Torit VS2400 Series No. 1939646.2X, 415 volts, cartridge type, bottom receptacle, approx 1300mm x 780mm x 1900mm(H). Note: Decommissioned, condition unknown
44	1	Electrolytic Pickler, Super Dek Inox 2003 Ricerca Chimica, Model SDI2003, 240 volt plug in, on fabricated steel trolley and assorted spare parts including hose, pads, etc
45	1	Twin Belt Grinding Machine, Kuhlmeier, Type ZBS, S/No. 0603101, DOM: 2006, 3000mm x 1000mm bed size, fitted with 2 x contact pressure tools, lanyard safety wire, overhead fluorescent work light 8kw, 415 volts. (1-71). Note: Extraction ducting not included
46	1	Twin Belt Grinding Machine, Kuhlmeier, Type ZBS2, S/No. 0401151, DOM: 2004, belt length approx 3000mm and pendant control, fitted with Infinitely Workpiece Handling Device and contact pressure tool, lanyard safety wire, overhead fluorescent work light, 8kw, 415 volts. (1-70). Note: Extraction ducting not included
47	1	Double Ended Pedestal Linisher/Grinder. Brobo Waldown, 415 volt hard wired with dust extraction ducting to first horizontal joint only. Fitted with 1 x linishing wheel. (1-72). Note: Tools required for removal
48	1	Double Ended Pedestal Linisher/Grinder, brand unknown, 415 volt hard wired with dust extraction ducting to first horizontal joint only. Fitted with 1 x buffing wheel and 1 x linishing wheel. (1-73)
49	1	Sand Blasting Cabinet, vertical, Toolex, pneumatic operation, 940mm x 700mm x 1500mm(H) with attached dust collector, Toolex, bag type, Model FM230, 750 watt, 240 volts. (1-74)
50	1	Pedestal Linisher, Grit, single head Model DK-7300, 700mm x 75mm belt, 415 volt plug in with assorted belts. (1-75)
51	1	Parts Barrel Tumbling Machine, Daesung Finishing Machinery Co. Model BT-200, 200 Ltr drum capacity, DOM: 2002, S/No. 20023.5, 1.5kW 240 volt hard wired, digital readout. Overall dimensions approx 1200mm x 1300mm x 1500mm(h) with transformer. (1-76) Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
52	1	Parts Barrel Tumbling Machine, Daesung Finishing Machinery Co. Model BT-200, 200 Ltr drum capacity, DOM: 2002, S/No. 20023.6, 1.5kW 240 volt hard wired, digital readout. Overall dimensions approx 1200mm x 1300mm x 1500mm(h) with transformer. Decommissioned.
53	1	Vibratory Bowl Finishing Unit, Daechang, Model 40/100, wall mounted control panel, bowl size approx 1000mm x 300mm. Full height approx 1000mm, 415 volt hard wired. (1-77) Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
54	1	Vibratory Bowl Finishing Unit, brand unknown, manual tilt, 415 volt hardwired, wall mounted control panel with timer, octagonal shaped bowl, approx 570mm AF x 270mm, full height approx 1400mm. (1-78) Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.

**Sale 5008321 - Preliminary Catalogue - Items May Be Subject to Change**

Lot No.	Units	Description
55	1	Vibratory Bowl Parts Finisher, BV Products, Model unknown, hardwired with wall mounted control panel, bowl size approx 760mm x 300mm, overall height approx 830mm(H). (1-79) Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
56	1	Sand Blasting Cabinet, Burwell, Model BCBC-915D, S/No. 706, pneumatic operation, features foot pedal control, electrical safety guarded door, approx 1560mm x 900mm x 1860mm with lifting lugs and attached abrasive extraction unit Burwell, filter type, 415 volt hard wired, approx 1400mm x 600mm x 2900mm with lifting lugs. (1-82) Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
57	1	Pedestal Linisher, GRIT, single head, model unknown, 700mm x 150mm belt size, 415 volts hardwired with provision only for extraction unit and assorted spare belts. (1-81) Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
58	1	Double ended bench grinder, Brobo Waldown, Model GP250, 415 volt hardwired 2800 rpm, mounted on metal pedestal base. (1-80) Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
59	1	Tool Grinder, Amada, Model unknown, 240 volt with transformer, approx 150mm dia. grinding wheel mounted on metal stand. (1-66)
60	1	Manual Fly Press, Spectral, Model C100, mounted on fabricated steel stand, (1-68)
61	1	Manual/Hydraulic Press, hand lever activated, capacity unknown, gauge reads to 14000 psi, overall dimension approx 800mm x 700mm x 1950mm.
62	1	Corrugating Jenny Wheel, Bramley Model 076, 240 volt plug in side mounted control box foot pedal control, (damaged) mounted on light weight sheet metal stand.
63	1	Sheet Metal Roller, unbranded, 3 x rollers, 1300mm x 75mm dia., manually adjusted, foot pedal control, side mounted emergency stop, approx 2000mm x 700mm x 1300mm(H), 240 volt plug in. (1-1)
64	1	Drill Press, Hafco, manual height adjustment, manual slow speed adjustment fitted with 65mm keyed chuck, 2HP motor, 415 volt plug in with manual adjustable 'T' slotted work bed, with X and Y axis, approx 700mm x 210mm, approx 1800mm overall height. (1-2)
65	1	Drill Press, Hafco, manual height adjustment, manual slow speed adjustment fitted with 1/2" keyed chuck, 2HP motor, 415 volt plug in with manual adjustable 'T' slotted work bed, with X and Y axis, approx 700mm x 210mm, approx 1800mm overall height. (1-2)
66	1	Spot Welder, Aston, Model 152 S/No. 2331TT, foot pedal operation, electrical/pneumatic, water cooled, 760mm neck capacity, fitted with Weltouch CY-210B Miyachi control panel, 25mm electrode, overhead fluorescent work light, 415 volt hard wired. Approx dimension 270 x 1500 x 1900mm. (1-7) Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
67	1	Spot Welder, Aston Model 162, S/No. 2729ACF foot pedal operation, electrical/pneumatic, water cooled 570mm throat capacity, fitted with Weltouch 04-210B Miyachi control panel, 25mm electrode, with 15mm dia. tip, overhead fluorescent work light with remote cooling unit, 415 volt hard wired, approx dimension 300mm x 1370mm x 2000mm(H). (1-8) Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
68	1	Metal Clinching Press, Tox, pneumatic operation, foot pedal control, 0.7mm thickness capacity, 200mm throat size, 240 volt plug in. Approx overall dimensions 870mm x 700mm x 1900mm(H). (1-9)
69	1	Notcher, IMAC, model unknown, 4mm thickness capacity, approx 210mm blade, manual adjustable notch size, foot pedal control, 415 volt plug in, 700mm work table with under drawer off cut receptacle 700mm x 800mm x 1050mm(H) overall dimensions.

**Sale 5008321 - Preliminary Catalogue - Items May Be Subject to Change**

Lot No.	Units	Description
70	1	Notcher Boschert, type PN4, S/No. 398, DOM: 1984, thickness unknown, manual adjustable notch size, foot pedal control, 415 volt plug in, 700mm work table with attached off cut receptacle, 715mm x 1120mm x 1200mm overall dimensions with top mounted lifting ring. (1-13)
71	1	Roll Warmer, DM Stuart, MK IV, Model No. CE184, thermal indicator light and adjustable temperature, 720mm x 490mm x 350mm overall dimension. (1-14)
72	1	Deburrer Fall Products, Model 131, mobile twin head manual adjustment, 240 volt plug-in, overall dimensions 1120mm x 670mm x 1200mm.
73	1	Spot Welder, Aston Electrical Model 119P, S/N 2223RF, water cooled, approx 760mm throat, foot pedal operation with Aston Model 1268 cooling unit (240 volt) with spare Bottom oven, 415 volt hardwired. (1-45) Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
74	1	Spot Welder, CIG Spotmatic, Type TAE93/17/30 BFO226 with offset tip, 760mm throat, Auto Weld top mounted analogue display control box, foot pedal control, 415 volts, overall 350 x 1400 x 1650mm(H). Note: Decommissioned, condition unknown. Located on Mezzanine Floor. (1-59)
75	1	Spot Welder, Uniting, mobile Spot Car 9000, throat approx 290mm with independent gun, hammer and pneumatic plier operation, digital control panel, 415 volt plug in.
76	1	Spot Welder, Aston Electrical Model 142, approx throat size 280mm with Weltouch digital display panel, foot pedal control. Note: No top arm or electrode, condition unknown, suit parts only. Located Mezzanine Floor
77	1	Spot Welder, brand unknown, Type PP15, approx throat size 350mm, foot pedal control. Note: Parts missing, electrode not included, condition unknown, suit parts only. Located Mezzanine Floor
78	1	Spot Welder, brand unknown, throat size approx 500mm, foot pedal control, 45 volts. Note: condition unknown, suit parts only
79	1	Spot Welder, EMF Model TAE40/15, S/No. BD0003 approx 620mm throat foot pedal control, digital display and control box (top mounted) top lifting lugs, approx overall dimensions 760mm x 1400mm x 2200mm, 415 volts with 2 x cooling units. Note: Bottom area and electrode missing, condition unknown, suit parts only. Located on Mezzanine Floor. (1-60)
80	1	Stud Welder, TRW, Series 4500, mobile, Model 101, 415 volt plug in with hand piece, earth lead and power cables
81	1	Stud Welder, Evico, PW900, 240 volt plug in with hand piece, earth and power leads
82	1	Ultra Violet Weld Tester, Spectroline, Model SB-100B/FA, 240 volt plug in with part container of fluorescent leak test fluid, and 2 x spare globes
83	1	Granite Surface Plate, 630mm x 400mm x 105mm on fabricated tubular steel table, 1030mm(H)
84	1	2 x Steel surface plates, 1 x 600mm x 450mm x 200mm(T) and 1 x 610mm x 455mm x 15mm(T) with 1 fabricated metal, 2 x tier trolley x 1040mm(H)
85	2	Rotating Sheet Metal Work Table, mobile, manual adjustment, 550mm x 550mm surface area, ball bearing rotating action, approx 1000mm to 1400mm adjustment (Note: Sold per each. Buyer to nominate quantity required)
86	1	Rotating Sheet Metal Work Table, mobile, manual adjustment, 500mm x 500mm surface area, ball bearing rotating action, approx 1000mm to 1400mm adjustment (Note: Sold per each. Buyer to nominate quantity required)
87	1	Magnetic Chuck, Eclipse magnetic, 600mm x 200mm surface area, manual operation. Note: Activating handle missing
88	1	Magnetic Chuck, Eclipse magnetic, 360mm x 160mm surface area, manual operation
89	1	Parts Washer, Kleentech Model KT4000, 240 volt plug in, dial panel, poly with hinged lid, approx dimensions 1000mm x 660mm x 1000mm
90	1	Stepladder, Welbilt, aluminium, double sided, 150kg capacity
91	1	Stock Picking Ladder, Little Giant, aluminium, 820mm platform height, rubber slip proof steps, 2 x rubber wheels, collapsible with balance support rail and pen tray
92	1	Platform Ladder, Bailey, aluminium, 1450mm platform height with balance support rail, 150kg SWL
93	1	Stepladder, Oldfield, 6ft aluminium, double sided, 150kg SWL

**Sale 5008321 - Preliminary Catalogue - Items May Be Subject to Change**

Lot No.	Units	Description
94	1	Stepladder, Oldfields Industrial, 7ft aluminium, 120kg SWL
95	1	Stock Picking Ladder, 'Little Jumbo' aluminium, 700mm platform height, rubber slip proof steps, 2 x rubber wheels, collapsible with balance support rail and pen tray
97	1	Communication Cabinet, Rack Technologies, beige and grey metal, smokey perspex door, mobile, 630mm x 800mm x 1630mm(H) with D-Link DES-1016D, alarm volume switch and Wintel SA25 public address amplifier
98	1	Kick Press, Raleigh, manual, cast steel, 520mm x 1350mm(H)
99	1	Punch and Die Grinder, Strippit Houdaille, 85010-000, 240 volt plug in, 2050 rpm, approx 400 x 550mm. Note: Chuck missing
100	1	Robotic Welding Cell, comprising 1 x Robotics Arm, Fanuc Robot Arc Mate 100, type AOSB 2354-B003 DOM: 1995, 1 x wall mounted Fanuc Systems R-J2 control panel and pendant control, S/No. R9S175781, 2 x wall mounted Hitachi wire feed units, wall mounted, type TM-351E, wire diameter 1.2 - 1.6mm(D), 1 x BOC WF4 wire feeder, wall mounted, 1 x Thermal Arc Ultima 150 plasma webber stand mounted, 2 x Hitachi Inverters 350 CXP11 welding pens source, floor mounted with assorted custom fabricated welding positioners and lockout gates, contained in cell with 9 x twin 40 watt flame proof fluorescent lights, fume extraction compatible hooded ceiling (no fan or ducting included), 3 x sliding safety switched doors, overall dimensions approx 6 mtrs x 5 mtrs x 3.8 mtrs(H) (1-40) Important Notes: 1) Extraction / removal of plant from this site must be undertaken in a manner compliant with all relevant NSW OH and S legislation / regulations and codes of practice. A satisfactory "Safe Work Method Statement" (SWMS example available in the OH and S section of the sale overview) and copies / evidence of insurances and licenses will be required prior to any work being undertaken. Pre approved contractors details are available on the overview.
101	1	Vertical Seam/TIG Welder Press, Amada ANT700W, DOM: 1987 with 1 x 2200TIG power source, 1 x Abicor Binzel coolant re-circulator, type WK23, 2 x foot pedal controls, push button and digital control panel bed, size approx 920mm x 920mm, 415 volt hard wired, overall size 920mm x 1700mm x 2550mm. (1-19) Note: This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
102	1	5 x Welding Bay Cells of approx 15 mtrs x 5 mtrs overall, galvanised steel frame, tracked welding curtains with 7 x head flex trunk adjustable fume extractors, 240 volts plug in, with approx 20 mtrs of ducting with 7 x exhaust chutes, fan system Aerotech Fans Model MVZ190, powered by 3 phase 15HP motor with assorted extractor head spare parts. (1-72) Important Notes: 1) The exhaust on this item will be disconnected from the roof and the roof repaired by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to collection that these works have been completed. 2) This unit requires you to work above 2 metres. Therefore you will need to comply with all Work at Heights Regulations. A Safe Work Method Statement (SWMS) may also be required. All requirements for Safe Work at Heights are to be met as per NSW OHS Act and Regulations. 3) This item will be disconnected from the electricity prior to removal by a licensed contractor engaged by GraysOnline. Purchaser/Contractor should confirm with GraysOnline site staff prior to commencing work on site.
103	1	Oxy Acetylene Set, including 1 x Uniflame torch, 1 x Comet welding head, 3 x gauges, welding nozzles, hose, with bottle trolley and storage box
104	1	Plasma Cutter Thermal Dynamics Pak Master 50, S/No. E71893A186408H, secondary 29A @ 100% duty cycle, cutting torch and earth lead, 415 volt plug in with fabricated metal trolley. (1-39)
105	1	TIG Welder, TIG Master, Kemppi, 2500w, ac/dc, 415 volt plug in, fitted with gas, water, test module, 210A, 29v @ 100% duty cycle with hand piece and earth lead, on trolley. (1-29)
106	1	TIG Welder, TIG Master, Kemppi, 2500w, ac/dc, 415 volt plug in, fitted with gas, water, test module, 210A, 29v @ 100% duty cycle with hand piece and earth lead, on trolley. (1-29)
107	1	TIG Welder, TIG Master, Kemppi, 2500w, ac/dc, 415 volt plug in, 210A, 29v @ 100% duty cycle, with hand piece and earth lead on trolley. (1-29)
108	1	MIG Welder, Kemppi, Pro Inox 500, Pro 400 power source, inbuilt wire feed with touch pad control 400A @ 100% duty cycle with hand piece, earth and gas leads on trolley, 415 volt plug in. (1-35)

**Sale 5008321 - Preliminary Catalogue - Items May Be Subject to Change**

Lot No.	Units	Description
109	1	TIG Welder, Miller Synchronwave 250DX, 165A, 16.2V @ 100% duty cycle, 415 volt plug in, digital readout with hand piece and earth lead and lifting lugs. (1-34)
110	1	TIG Welder, Miller Synchronwave 250DX, 165A, 16.2V @ 100% duty cycle, 415 volt plug in, digital readout with hand piece and earth lead and lifting lugs. (1-34)
111	1	TIG Welder, Miller Synchronwave 250DX, 165A, 16.2V @ 100% duty cycle, 415 volt plug in, digital readout with hand piece and earth lead and lifting lugs. (1-34)
112	1	TIG Welder, Miller Synchronwave 250DX, 165A, 16.2V @ 100% duty cycle, 415 volt plug in, digital readout with hand piece and earth lead and lifting lugs. (1-34)
113	1	MIG Welder, WIA 335 Weldmatic Model CP113-2 200A, 26V @ 100% duty cycle, fitted with 2 RD Weldmatic W55-0 wire feeder, hand piece, earth and gas leads on trolley, 415 volt plug in. (1-33)
114	1	MIG Welder, WIA 335 Weldmatic Model CP113-2 200A, 26V @ 100% duty cycle, fitted with 2 RD Weldmatic W55-0 wire feeder, hand piece, earth and gas leads on trolley, 415 volt plug in. (1-33)
115	1	MIG Welder, WIA 335 Weldmatic Model CP113-2 200A, 26V @ 100% duty cycle, fitted with 2 RD Weldmatic W55-0 wire feeder, hand piece, earth and gas leads on trolley, 415 volt plug in. (1-33)
116	1	MIG Welder, WIA 335 Weldmatic Model CP113-2 200A, 26V @ 100% duty cycle, fitted with 2 RD Weldmatic W55-0 wire feeder, hand piece, earth and gas leads on trolley, 415 volt plug in. (1-33)
117	1	MIG Welder, CIG TransMig 330, Model 705085, digital readout, 177A, 24.6v @ 100% duty cycle, with hand piece and earth lead, fitted with TransMig 2R Model 704841 on trolley, 415 volt plug in. (1-36)
118	1	MIG Welder, CIG TransMig 330, Model 705085, digital readout, 177A, 24.6v @ 100% duty cycle, with hand piece and earth lead, fitted with TransMig 2R Model 704841 on trolley, 415 volt plug in. (1-36)
119	1	TIG Welder, Miller Synchronwave 250, 200A, 28v @ 60% duty cycle, 415 volt plug in, with hand piece only (no adaptor or earth lead). (1-37)
120	1	MIG Welder, CIG TransMig 210, Model 704832, 104A, 19.7v @ 100% duty cycle, 240 volt plug in with hand piece, earth and gas leads, built in wire feeder, lifting lug, on trolley. (1-38)
121	1	Plasma Welding System Thermal Arc, Ultima-150, "The Super TIG Performer", 415 volt plugged with hand piece and earth lead, plasma and shield gauges.
122	1	Plasma Welding System Thermal Arc, Ultima-150, "The Super TIG Performer", 415 volt plugged with hand piece and earth lead, plasma and shield gauges.
123	1	3 x MIG Welders, Cigweld, comprising 2 x TransMIG 210se and 1 x 330se, with built in wire feeders, 415 volts, Note: Condition unknown, suit parts only
124	1	Pallet of assorted welding consumables, including regulators, tips, shields, hand pieces, torches, leads, helmet and assorted MIG welding wire
125	1	Welders Bench, heavy duty tubular steel frame, 10mm thick plate steel top with undershelf, overall dimensions 2400mm x 1200mm x 900mm(H). (1-31)
126	8	Retractable Hose Reel, Gartec, wall mount with 15 mtrs of 1/2" air hose, 75 bar pressure rating. Sold per each. Buyer to nominate quantity required.
127	1	Retractable Hose Reel, AK Reels. Approx 12 mtrs of 1/2" hose, wall mount. Sold per each. Buyer to nominate quantity required.
128	1	Retractable Hose Reel, Gartec, wall mounted with 15 mtrs of 1/2" air hose, 75 bar pressure rating. Note: Tools required for removal
129	1	Retractable Hose Reel, Gartec, wall mounted with 15 mtrs of 1/2" air hose, 75 bar pressure rating. Note: Tools required for removal
130	1	Retractable Hose Reel, Gartec, wall mounted with 15 mtrs of 1/2" air hose, 75 bar pressure rating. Note: Tools required for removal
131	1	Retractable Hose Reel, Gartec, wall mounted with 15 mtrs of 1/2" air hose, 75 bar pressure rating. Note: Tools required for removal
132	1	Retractable Hose Reel, Gartec, wall mounted with 15 mtrs of 1/2" air hose, 75 bar pressure rating. Note: Tools required for removal
133	1	Retractable Hose Reel, Gartec, wall mounted with 15 mtrs of 1/2" air hose, 75 bar pressure rating. Note: Tools required for removal



**Sale 5008321 - Preliminary Catalogue - Items May Be Subject to Change**

Lot No.	Units	Description
134	1	Retractable Hose Reel, Gartec, wall mounted with 15 mtrs of 1/2" air hose, 75 bar pressure rating. Note: Tools required for removal
135	1	Retractable Hose Reel, Gartec, wall mounted with 15 mtrs of 1/2" air hose, 75 bar pressure rating. Note: Tools required for removal
136	1	Retractable Hose Reel, Gartec, wall mounted with 15 mtrs of 1/2" air hose, 75 bar pressure rating. Note: Tools required for removal
137	1	Retractable Hose Reel, Gartec, wall mounted with 15 mtrs of 1/2" air hose, 75 bar pressure rating. Note: Tools required for removal
150	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
151	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
152	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
153	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
154	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
155	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
156	1	Industrial Wall Fan, ABG, 2 x blade, 600mm, 240 volt plug in. Note: Tools required for removal
157	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
158	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
159	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
160	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
161	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
162	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
163	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
164	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
165	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
166	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
167	1	Industrial Wall Fan, AC Pro 2 x blade, 600mm, 240 volt plug. Note: Tools required for removal
168	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
169	1	Industrial Wall Fan, ASK, 2 x blade, 600mm, 240 volt plug in. Note: Tools required for removal
170	1	Industrial Wall Fan, Hydor, 2 x blade, 600mm, 240 volts plug in. Tools required for removal.
171	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
172	1	Industrial Wall Fan, Ebony, 2 x blade 600mm, 240 volt plug in. Note: Tools and ladder required for removal
173	1	Industrial Wall Fan, ABG, 2 x blade, 600mm, 240 volt plug in. Note: Tools required for removal
174	1	Industrial Wall Fan, ABG, 2 x blade, 600mm, 240 volt plug in. Note: Tools required for removal





