

DTR-30.1

2-ZONE, 7.2 CHANNEL SURROUND RECEIVER



FEATURES

AMPLIFICATION:

- 7 x 110 Watts/Channel at 6Ω
- 7 x 90 Watts/Channel at 8Ω
- Discrete Output Stages for All Channels
- Wide Range Amplifier Technology WRAT (5 Hz 100 kHz)
- Optimum Gain Volume Circuitry
- · High Current Power Supply (H.C.P.S.)

PROCESSING:

- HDMI™ (v1.3a to Support 1080p, Deep Color™, x.v. Color™, LipSync, DVD-Audio, Super Audio CD, Multichannel PCM)
- Dolby® TrueHD, & Dolby® Digital Plus Decoding
- Dolby® ProLogic IIz for Front Height Channels
- · DTS-HD® Master Audio, DTS-HD® High-Res Audio Decoding
- HDMI Video Upscaling (to 1080i) with Faroudja DCDi Edge™*
- Advanced TI (Aureus[™]) 32-bit Processing DSP Chip
- 192 kHz/24-Bit Audio DACs for All Channels
- Audyssey 2EQ™ Automatic Room Calibration and Correction
- Audyssey Dynamic EQ[™] for Loudness Correction
- Audyssey Dynamic Volume[™] for Optimal Listening Levels & Dynamic Bange
- 4 DSP Modes for Gaming (Rock, Sports, Action, Role Playing)
- A-Form Listening Mode Memory & IntelliVolume Input Level Calibration System
- Music Optimizer to Enhance Compressed Music Files
- Auto Input Detect Function
- · Independent Crossover Adjustment for F/FH/C/S/SB
- A/V Synchronization Function (up to 100 ms in 5 ms Steps)
- * From component video and composite video inputs via HDMI output

CONNECTIONS:

- · HDMI (6 Inputs (1 on Front Panel) & 1 Output)
- HD Component Video Switching (2 Inputs & 1 Output)
- Universal Port for Single-Cable Connection of Optional U-Port Dock for iPod and/or HD Radio Tuner
- · Color-Coded 7.2-Multichannel Pre Outs
- · Assignable Digital Inputs (2 Optical / 2 Coaxial)
- Front Panel A/V Inputs

CUSTOM INTEGRATION FEATURES:

- · Bi-directional Ethernet & RS232 Port for Control Systems
- Powered Zone 2 and Zone 2 Pre Out; Independent Control for Balance & Bass/Treble
- Max & Power On Volume Settings for Main Zone & Zone 2
- IntelliZone for Second Room Playback & Control
- Dealer Settings Memory Store & Recall with Lock/Unlock
- Permanently Stored Memory Settings
- 2 IR Inputs & 1 Output
- •3 Unique Assignable IR Code Sets
- 3 Programmable 12V Triggers (with Adjustable Delay)
- RIHD Remote Interactive over HDMI (supports HDMI CEC)
- PreProgrammed RI Remote Control with OSD Set-up
- Optional Rack Mount Kit Available IRK-155-3B



2-ZONE, 7.2 CHANNEL SURROUND RECEIVER





HOMI

SPECIFICATIONS

DOLBY. TRUETE

PRO LOGIC IIz



FAROUDJA DCDI EDGE



















AMPLIFIER

Continuous average power output (FTC)

90 W per channel min. RMS at 8Ω , All channels:

> 2 channels driven from 20 Hz to 20 kHz with no more than 0.08% total

harmonic distortion.

110 W min. RMS at 6Ω , 2 channels driven from 1 kHz with no more than

0.1% total harmonic distortion.

Dynamic power output (stereo): $2 \times 210 \text{ W}$ at 3Ω

 $2 \times 180 \text{ W}$ at 4Ω $2 \times 110 \text{ W}$ at 8Ω

Frequency response: 5 Hz to 100 kHz: +1/-3 dB Signal-to-noise ratio: 106 dB (LINE, IHF-A) Total harmonic distortion: 0.08% at rated power

Damping Factor: 60 (Front, 1 kHz, 8 Ω) Speaker impedance: 6Ω to 16Ω

INPUT SENSITIVITY AND IMPEDANCE

Line: 200 mV, 47 $k\Omega$

DUTPUT LEVEL AND IMPEDANCE

Rec out: 200 mV, 470Ω Pre out: 1 V, 470Ω Zone 2 line output: 100 mV, 470Ω

TONE CONTROL

±10 dB at 50 Hz Bass: Treble: ±10 dB at 20 kHz

FΜ

Tuning range: 87.5-107.9 MHz (100-kHz steps)

AM

Tuning range: 530-1,710 kHz (10-kHz steps)

GENERAL

Power supply: AC 120 V, 60 Hz

Power consumption:

Dimensions (W x H x D): 17-1/8" x 6 7/8" x 12 7/8"


435 x 175 x 327.6 mm

Weight: 24.0 lbs. (10.9 kg)

Optional mounting kit: IRK-155-3B

U dimension: 4U

435 [17.13]



326.5 [12.854] 42.3 [1.665] 262.5 [10.335] 184.5 [7.264] 40 [1.575]

Due to a policy of continuous product improvement, Integtra reserves the right to change specifications and appearance without notice.

Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.
DTS is a registered trademark & the DTS logos and Symbol are trademarks of DTS, Inc.
HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.
Manufactured under license from Audyssey Laboratories. U.S. and foreign patents pending.

2EG, Dynamic EO and Dynamic Volume are trademarks of Audyssey Laboratories.

The trademark of Apple Inc., registered in the U.S. and other countries.: Aureus is a trademark of Texas Instruments. x.v.Color is a trademark of Sony Corporation.

WRAT, Theater-Dimensional, CinemaFILTER and Music Optimizer are trademarks of Onkyo Corporation.

All other trademarks and registered trademarks are the property of their respective holders