

Hazard Register



Type	GARBAGE COMPACTOR TRUCK	Location	
Make	HINO	Sale Number	8013387
Model	-	Lot Number	8
Serial Number			

ID	Hazard Type	Hazard Description
122575.1	SLIP TRIP FALL	ENSURE WORKSPACE AROUND PLANT IS KEPT CLEAR OF OBSTACLES AND MAINTAINED IN A NEAT AND TIDY CONDITION.
122575.2	Signage	OPERATOR INJURY MAY RESULT FROM ILLEGIBLE OR MISSING WARNING LABELS/SIGNAGE (NOISE, PPE, OPERATING INSTRUCTIONS, HOT SURFACES, EXITS, ROTATING FANS, NIP POINTS ECT). REGULAR INSPECTION & REPLACEMENT OF WARNING LABELS (SAFETY DECALS) IS REQUIRED.
122575.3	Manual Handling	OPERATOR SPRAINS AND/OR STRAINS FROM MANUAL HANDLING WORK PIECES/PRODUCT ON AND OFF PLANT ITEM OR AS A RESULT OF REPETITIVE BODY MOVEMENT.
122575.4	PPE	PPE. PERSONAL PROTECTIVE EQUIPMENT (PPE) - IDENTIFY TYPE AND PROVIDE INSTRUCTION/INFORMATION RE: USE, STORAGE, CARE AND MAINTENANCE OF PPE (E.G. EYE & HEAR PROTECTION, DUST MASK ETC.)
122575.5	Signage	NEEDS HAZARD WARNING SIGN NEEDS TO BE ATTACHED RE USE EYE & HEARING PROTECTION REQUIRED. THERE ARE REAR TRANSPORT DECALS ON THIS PLANT.
122575.6	Guarding	MOVING PARTS OF PLANT MAY ENTRAP OR CUT BODY PARTS. ALL FIXED AND OPERABLE GUARDS MUST BE REPLACED AFTER MAINTENANCE/CLEANING ACTIVITIES. GUARDING SHOULD BE IN ACCORDANCE WITH AS4024.1: SAFEGUARDING OF MACHINERY.
122575.7	Potential Energy Release	UNCONTROLLED RELEASE OF STORED SPRINGS, TENSION SHAFTS, COUNTER WEIGHTS, OBJECTS STORED AT HEIGHTS, OBJECTS STORED UNDER HYDRAULIC/PNEUMATIC PRESSURE & ELECTROMAGNETIC DEVICES.
122575.8	Noise	SOUND PRESSURE LEVEL (SPL) NEEDS TESTING AT OPERATOR STATION. IF SPL GREATER THAN 85dB(A), CLEAR & VISIBLE WARNINGS MUST BE ATTACHED re: USE OF HEARING PROTECTION
122575.9	Guarding	ENSURE ANY SAFETY ISOLATION SWITCHES ATTACHED TO OPERABLE GUARDS ARE REPOSITIONED AND TESTED ON A REGULAR BASIS AS PER GUARDING STANDARD AS 4024.
122575.10	Electrical	PLANT TO BE USED IN CONJUNCTION WITH EARTH LEAKAGE CIRCUIT BREAKER (SAFETY SWITCH) AND OVERLOAD PROTECTION.
122575.11	Electrical	PLANT NEEDS TO BE REGULARLY INSPECTED AND MAINTAINED AS PER AS/NZS3760: IN-SERVICE SAFETY INSPECTION AND TESTING OF ELECTRICAL EQUIPMENT AND AS/NZS3000: WIRING RULES AND/OR AS1543: ELECTRICAL EQUIPMENT OF INDUSTRIAL MACHINES.
122575.12	Crushing	COMING INTO CONTACT WITH MOVING PARTS OF THE PLANT DURING TESTING, INSPECTION, OPERATION, MAINTENANCE, CLEANING AND REPAIR. ENSURE SIGNAGE IS ATTACHED TO PLANT INSTRUCTING OPERATOR TO "KEEP BODY PARTS (HANDS ECT) CLEAR DURING PLANT OPERATION.
122575.13	Signage	HAZARD WARNING SIGN RE " KEEP HANDS CLEAR OF IMPACT/CRUSHING AREA " TO BE ATTACHED.
122575.14	Access	ACCESS TO BE RESTRICTED TO AUTHORISED AND TRAINED PERSONNEL ONLY. FIT HAZARD WARNING SIGNS (AS APPROPRIATE) TO PREVENT ACCESS TO DANGER ZONES.

Hazard Register

122575.15	Instructions	ATTACH OPERATING INSTRUCTIONS IN A CLEAR AND VISIBLE POSITION TO OPERATOR.
122575.16	Plant Maintenance	ISOLATE AND DE-ENERGISE POWER/ENERGY (ELECTRICAL & HYDRAULIC) SUPPLY TO THE PLANT BEFORE CLEANING, DISMANTLING AND MAINTENANCE IS CARRIED OUT ON THE PLANT
122575.17	Plant Controls	OPERATOR INJURY MAY RESULT FROM POORLY LABELLED / UNLABELLED OR INCORRECTLY LABELLED CONTROLS. ENSURE ALL OPERATIONAL CONTROLS ARE CLEARLY IDENTIFIED AND LABELED.
122575.18	Emergency Stop	AN EMERGENCY STOP BUTTON IS PRESENT ON THIS PLANT. ENSURE THAT THE EMERGENCY STOP BUTTON IS REGULARLY CHECKED FOR CORRECT OPERATION.
122575.19	HIGH PRESSURE FLUID.	HYDRAULIC FAILURE. ENSURE THAT THE HYDRAULIC LEAK IS REPAIRED PRIOR TO USE IN THE WORKPLACE.
122575.20	Plant Structure	WORK AT HEIGHTS. ENSURE THAT THE LADDER AND HANDRAILS ARE SECURED AND MEET THE REQUIREMENTS AS PER AS1657.2013 FIXED PLATFORMS, LADDERS & STEPS.

Health and Safety Plant Safety Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

Likelihood	Consequences
<ul style="list-style-type: none">• Frequency and duration of exposure• Probability of occurrence of hazard or event (including part history of incidents)• Possibility to avoid / minimize or limit the damage, impact or harm• Reliability and effectiveness of existing / established systems of control	<ul style="list-style-type: none">• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area• Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.